

# AMP20068 SOLID STATE HIGH POWER AMPLIFIER

## FEATURES

Designed for EMI/RFI, lab, CW/Pulse and all EW communication applications  
 Small form factor, rack mounted system  
 Class A/AB Linear design  
 High Power Advanced technology devices  
 Instantaneous ultra-wide bandwidth  
 Built-in protection circuits, with extensive monitoring  
 Local LCD & remote flexible interfaces  
 High efficiency, with unprecedented reliability and ruggedness  
 LEGACY PN: AMP2065A-1LC



## ELECTRICAL SPECIFICATIONS : 50Ω, 25°C

Parameter	Specification	Notes
Operating Frequency Range	6.0 - 18.0 GHz	
Power Output @ Psat	200 Watt Min	CW or Pulse
Power Output @ PldB	-	
Power Gain	53 dB Min	0dBm or less for rated Pout
Power Gain Flatness	5.0 dB p-p Max	Constant input power
Gain Adjustment Range	20 dB Min	Local or remote capable
Input / Output Return Loss	-10 dB Max	
2-Tone Intermodulation (IMD)	-30 dBc Typ	43dBm/Tone, Δ = 1MHz
Harmonics	-20 dBc Typ	At rated output power
Spurious	-60 dBc Max	Non-harmonics
Operating Voltage	120/208 VAC, 3-Ph, 47 - 63 Hz	Opt: 230/400VAC, 3-Ph
Power Consumption	4000 Watt Max	At rated Pout
Input Power Protection	+3 dBm Max <sup>1</sup>	
Load VSWR Protection	4 : 1: Max <sup>2</sup>	Foldback @ preset limit
Sample Port	-50 dB	N-Female

<sup>1</sup> Units with optional digital monitor and control, for basic units <10 Sec without damage

<sup>2</sup> Units with optional digital monitor and control, for basic units <1 minute at rated Pout

## ENVIRONMENTAL CHARACTERISTICS

Parameter	Specification	Notes
Operating Ambient Temperature	0 to +50 °C	
Storage Temperature	-40 to +85 °C	
Relative Humidity	up to 95 %	Non Condensing
Altitude	3000 meters	
Shock & Vibration	Normal transport <sup>3</sup>	

<sup>3</sup> MIL Spec available for quotation

## MECHANICAL SPECIFICATIONS

Parameter	Specification	Notes
Dimensions W x H x D	421 x 308 x 700 mm	7U - excluding connectors
Weight	48 Kg. Typ	
RF Conn. In / Out / Sample	N-Female / WRD650 / N-Female	Rear panel
Interface Connector	9-Pin D-Sub	Rear panel
AC Power	MS-Style	Or equivalent
Cooling: Built in Quiet-Cool	Close circuit Air-liquid cooling	60-65 dBa Typ
<b>OPTIONAL:</b> Digital Monitor & Control (DMC <sup>4</sup> ) FWD, REV, VSWR, GAIN, ALC, V & I, TEMP, Optional Safety Interlock (INT)	Ethernet RJ-45 TCP/IP, RS422/485, USB Optional GPIB Interface Open=STBY/Short=RFON	IEEE rear panel BNC-F rear panel

<sup>4</sup> DMC option may reduce Pout by 0.5dB.

# AMP20068 SOLID STATE HIGH POWER AMPLIFIER

### AVAILABLE SPECIAL OPTIONS

Parameter	Specification	Notes
Option FRS: Forward RF Sample	-60dB, Type N-Female	Front or rear panel
Option RRS: Reflected RF Sample	-50dB, Type N-Female	Front or rear panel
Option GPIB: GPIB remote control	GPIB IEEE-488 Remote capability	
<b>Included CPM:</b> Calibrated Power Monitoring (With purchase of Option DMC)	Offset correction entry for +/- 0.2dB accuracy	11-points standard <sup>5</sup>

<sup>5</sup> Consult the factory if additional points are required.

### OUTLINE DRAWING SHOWN WITH LCD DIGITAL CONTROLLER

